



Solar Wall Mounted LiFePo4 Battery 100ah 200ah 5kwh 10kwh Lithium Battery 48V

Our Product Introduction

for more products please visit us on enikolnewenergy.com


Basic Information

- Place of Origin: Guangdong, China
- Brand Name: ENIKOL
- Model Number: ESK4810CW/ESK4820CWP/ESK4820CW
- Minimum Order Quantity: 2 sets
- Price: \$800.00/sets 2-9 sets
- Packaging Details: package
- Supply Ability: 2000 Piece/Pieces per Week





Product Specification

- Weight: 47kg/74kg/85kg
- The Charging Ratio: 0.5C
- The Discharge Rate: 1C
- Storage Type: Standard Storage
- Anode Material: LFP
- Application: Home Appliances, Consumer Electronics, BOATS, Golf Carts, SUBMARINES, Electric Bicycles/Scooters, Electric Vehicles, Electric Wheelchairs, Electric Power Systems, Solar Energy Storage Systems, Uninterruptible Power Supplies, Electric Forklifts
- Type: Wall Mounted
- Rated Capacity: 100AH(5120WH)/ 184Ah(9420.8WH)/ 200AH(10240WH)
- Rated Voltage: 51.2V
- Display: LCD
- Cycle Life: ≥8000 Times



More Images





Product Description

Lifepo4 Power Wall 48v battery 100ah 200ah Home Solar 5kwh 10kwh Lithium Battery Energy Systems



Widely Applications:

1. EV, e-scooter, electric golf car, electric vacuum sweeper.
2. Electronic toy, model airplane, remote control.
3. Communication equipment: Cordless telephone, inter-phone.
4. Modality equipment and consumer electronics.
5. Decorative lighting, Solar lamps, torch, emergency light, solar street light and power supply.

Product Model:	ESK-4810CW	ESK-4820CWP	ESK-4820CW
Type of Battery:	Lithium Iron Phosphate		
Max parallel:	16/64sets		
Rated capacity:	100AH (5120WH)	184AH (9420.8WH)	200AH (10240WH)
Rated voltage :	51.2V		
Charging voltage:	58.4V		
Max charging current :	100A		
Max continuous discharge current:	100A/150A optional		
Weight:	47kg	74kg	85kg
Display:	LCD		
Dimension (L* W * H) mm:	620*460*195	850*455*180	955*460*195
Warranty :	5 years		
communication faction:	CAN/RS485/RS232		
Cycle life:	≥6000 times	≥8000 times	≥6000 times
Operating temperature:	-20 to +65		
Protection function:	overcharge protection, over discharge protection, over-current protection, short circuit protection, over temperature protection and low voltage alarm		
Matched solar inverter brands:	PYLONTECH/GOODWE/Growatt/SMA/Victron/TBB/Must/Srne/MEGARE VO/Deye/INVT/Voltronic/SOFAR/SOROTEC etc.		
Bluetooth function	Optional		



Schematic Diagram of Energy Storage System Connection



Why Choose Us

About Us

OEM/ODM
energy storage
battery source factory



Factory



Exhibition



ENIKOL Damien New Energy Technology (Shenzhen) Co., Ltd.

86 17727596282

andy@enikolnewenergy.com

enikolnewenergy.com

Guangming District, Shenzhen, Guangdong Province, China